

## WAVES

### TECHNICAL PROPERTIES

#### HARDWEARING

Resistente all'usura | Strapazierfähig  
 Résistant | Slitesterkt  
 Kulutusta Kestävä | Resistente

#### ELEGANTLY COMFORTABLE

Confort con Stile | Schön und Komfortabel  
 Beau et Comfortable | Vakkert & Behagelig  
 Tyylikäs & Mukava | Agradable y Comfortable

#### BREATHABLE

Traspirante | Atmungsaktiv  
 Respirant | Pustende  
 Hengittävä | Transpirable

#### EASY CARE

Facile Manutenzione | Pflegeleicht  
 Facile d'entretien | Lettstelt  
 Helppohoitoinen | Fácil Mantenimiento

#### ECOLOGICALLY FRIENDLY

Ecologica | Umweltfreundlich  
 Écologique | Miljøvennlig  
 Ympäristöystävällinen | Ecológico

#### COMPOSITION

88% Polyester  
 12% Polyurethan  
 Materiale | Zusammensetzung  
 Composition | Komposisjon  
 Koostumus | Material

#### WIDTH

142 ± 2 cm  
 Larghezza | Breite  
 Laize | Bredde  
 Leveys | Largo

#### WEIGHT

265 g /m<sup>2</sup> ± 15%  
 Peso | Gewicht  
 Poids | Vekt  
 Paino | Peso

#### ABRASION

≥ 40.000 martindale  
 ISO 12947-1-2-3-4  
 Abrasione | Abriebfestigkeit  
 Abrasion | Slitestykke  
 Hankauskesto | Abrasión

#### LIGHTFASTNESS

≥ 5 blue scale (SCALE 1-8)  
 ISO 105 B02  
 Solidità alla Luce | Lichtechtheit  
 Tenue à la Lumière | Lysekthet  
 Valonkesto | Solidez a la Luz

4 / 4 (Wet/Dry)

3-4(Wet) only dark colors  
 ISO105X12-DIN54021

#### RESISTANCE TO RUBBING

Resistenza agli sfregamenti | Reibechtheit  
 Solidité des Tintes | Gniekthet  
 Värinkesto | Resistencia al Frotamiento

#### PILLING

5 (scale 1-5)  
 ISO 12945-2  
 Pilling | Pilling  
 Pilling | Pilling  
 Nyppyntyminen | Pilling

#### CLEANING

60°  
  
 Pulizia | Reinigung  
 Nettoyage | Rengjøring  
 Puhdistus | Limpieza

#### FLAMMABILITY

BS 5852 P.1 source 0  
 California Bull. 117 Sec. E.  
 Infammabilità | Schwerentfambarkeit  
 Non feu | Flammesikring  
 Paloluokitus | Infamabilidad

Can be F.R. treated to pass:  
 FAR 25.583 - UFAC CLASS 1  
 NFPA 260 CLASS 1 BS 5852 - CRIB 5  
 ASTM E 662/03

